



The 8' Cedar Shake is unique in offering a multitude of enhanced features, built into one full length panel ensuring faster and effortless installations. Its detail in composition provides a lasting traditional look to any structure.

Noviskake RS8 offers the look of traditional craftsmanship engineered to replicate the natural texture of wood without the inconveniences. We guarantee products of exceptional durability and great performance.

/ COLORS AVAILABLE

WHITE #001	PRAIRIE WHEAT #017	KHAKI #018	ACADIA #032	SIERRA #034	YELLOWSTONE #035	HERITAGE GRAY #063	SANDSTONE #064	PINE #065	OAK #301	OLIVE #302
SLATE #067	UMBER #071	COBALT #075	EVERGREEN #076	SAND #078	SAGE #132	WEATHERED BLEND #201	CEDAR BLEND #202	TRADITIONAL BLEND #203	WALNUT #303	TEAK #304
GRAY BLACK BLEND #206	CANYON BLEND #208	BASALT #229	BROWNSTONE #231	ANTHRACITE #233	BURNISHED SLATE #682	ROCKAWAY GRAY #925	COFFEE BEAN #926	EBONY #305	SEQUOIA #306	

Stainnatural
colors



ENHANCED PERFORMANCE FEATURES



/ What is Fast-Fit?

Features that simplify installation.




"Nail Locators" facilitate the installation by precisely showing nail position.



"Hammer-Stopper" system limits nail penetration to ensure smooth panel expansion and contraction.



The center-panel nailing hole helps spread the panel's expansion and contraction evenly.



Horizontal expansion stoppers are positioned for an exact and proper installation.



Product shown: NOVISHAKE™RS8 - 8' Cedar Shake Sandstone #064 / Overall dimensions: 96.5" X 8.5" (245,11 cm x 21,59 cm)
22 panels each box: 96.41 square feet (8,96 m²) / 4.4 ft² (0,41 m²) per panel



EXCLUSIVE to **NOVIK®** a **continuous** full panel **interlocking system** for secure and rapid installation.



The panel's vertical interlocking system permits faster and easier installation, and alignment.




Authentic cedar wood texture.



Corners are available in all NOVISHAKE™RS8 colors.

FEATURES AND BENEFITS

- Extreme temperature variation resistance
- Resistance to warping, expansion, contraction and cracking
- Wind and Impact (ASTM D4226) resistance
- Resistance to discoloration (U.V rays.)
- Flame spread <200
- Seamless visual appearance
- Lightweight material, fast and easy to install
- Virtually maintenance free
- Never needs to be painted
- Authentic wood texture
- Armonizes with all siding types
- Features that simplify installation 
- Certified testing by independant laboratories (ICC-ES, FBC, CCMC)

TESTS

Test	Standard testing	Result for NOVIPLANK™RS8
Fire rating	In accordance with ASTM E84	Flame spread < 200
Impact	In accordance with ASTM D4226	>35 in-lbf
Weatherability	In accordance with ASTM D1435/G147	Pass
Wind	In accordance with ASTM D5206	Resist to wind speed of 110 MPH (177 km/h) minimum (depending on product)*

All testing in accordance with ICC-ES AC308 (Acceptance criteria for polymer siding systems)
Product certified by independant laboratories

* Contact Novik customer service for additional information

ABOUT NOVIK®

Novik® provides beautiful shakes and stone that faithfully reproduce traditional materials at the cutting edge of technology, offering an option that is both attractive and easy to install, and provides tremendous value. Novik® products are a perfect fit for consumers who take pride in the natural beauty of their home, while demanding the freedom and lifestyle that little to no upkeep for our products provides. With Novik®, discover a multitude of possibilities for the residential and commercial construction sectors as well as the renovation industry.

For more information : www.novik.com.

Distributed by:

MITTEN®
par/by PLY GEM

1-888-MITTEN4 mittenbp.com

460120004A / 07-2015 / Printed in Canada
© Copyright NOVIK® 2015

